

Console C



Installation guide april 2008

BEFORE YOU BEGIN

Your choice is a testimonial to your excellent taste. Thank you for choosing from among WETSTYLE's quality line of products. We recommend that you carefully read this guide to ensure that your console table with integrated lavatory is properly installed and reliable for many years to come.

TOOLS AND EQUIPMENT



RECOMMENDATIONS - INSTALLATION

Before packaging, the console and integrated washbasin have received a double inspection for quality.

The console is made of high quality stainless steel of superior durability. Caution: this material can easily be scratched with blunt instruments used for the installation. We strongly recommend that you leave on the sticker paper covering the whole surface of the stainless steel console before completing all the operations of plumbing installation. NEVER USE BLUNT INSTRUMENTS TO TAKE OFF THE STICKER PAPER.

The glass shelf, packed individually, is dedicated to storage under the washbasin. It has been temporarily fixated atop the washbasin for delivery. Remove the glass shelf and put it safely aside, vertically, until the installation of console and washbasin is completed. This glass shelf fits perfectly into the stainless steel structure placed underneath the washbasin. You do not need to add any sealing material.

The integrated washbasin is screwed onto the console. It has been prepared to include the faucets, which will be installed directly on the washbasin. You may not have requested pre-piercing for the faucet holes at the time of purchase. We recommend you unbolt the integrated washbasin to allow the plumber to drill the faucet holes. To drill holes in the washbasin prior to plumbing installation, please consult the section Instructions – faucet holes in annex document.

Levelling is done using the 4 levellers at the console base.

Fastening the console to the wall. There are holes on the upper back tubular element, to hold the console. Please use standard fasteners according to existing mural coating.

Plumbing must be installed according to all local building and plumbing current national regulations. When proceeding to installation of basic plumbing – water inlet and area drain – follow closely manufacturer instructions for proper installation. Check leak-tightness of connections before final installation. Proceed to final connecting of plumbing pipes. Connect water to plumbing.

2 WETSTYLE

april 2008 Installation guide

CLEANING GUIDE - integrated countertop

Your WETSTYLE countertop is manufactured with WETMAR™; an ultra-smooth, non-porous material that helps keep grime and calcium deposits in check. WETMAR™ is ultra-easy to clean—after each use, simply wipe with a soft cloth to remove any surface dirt. For standard cleaning of both glossy and matte finishes, we recommend using widely available cleaning products such as Mr. Clean, Fantastik, CIF, etc. The matte finish may occasionally require a mildly abrasive product as soft scrub. Never use petroleum-based products when cleaning, i.e. paint thinners or other solvents, as they may damage surface. (Note: Personal hygiene products and cosmetics will NOT damage the surface.)

Standard Cleaning

WETMARTM, glossy finish:

Wipe surface with a soft cloth after each use. Use a mild cleaning product such as Mr. Clean, Fantastik, CIF, etc.

Do not use abrasive products or cream cleansers.

WETMARTM, matte finish:

Wipe surface with a soft cloth after each use. Use a mild cleaning product such as Mr. Clean, Fantastik, CIF, etc.

For more difficult stains, use a mildly abrasive cream cleanser such as Soft Scrub, Comet Soft Cleanser, Cream with Bleach or CIF.

Scratched or Damaged Surfaces

To repair scratched or damaged surfaces, sand the area using 600-, 800- and 1200-grit sandpaper: begin with the lower number (coarser) grit followed with each higher number (finer) grit in ascending order. Finish by polishing the surface using a cloth and white polishing compound for automobiles.

MAINTENANCE GUIDE - Stainless steel console

Console C is built in stainless steel, a high quality corrosion-resistant material requiring easy and regular care for durability.

After each use, just wipe the console with soft tissue to take off dirt. It is important to keep your console clean, without any dirt, oil or deposits.

For regular maintenance, we recommend a mix of water and white vinegar (80% water + 20% vinegar), super soft soap or glass cleaner. Spread liquid with soft tissue. It is important to <u>rinse with fresh water and dry thoroughly</u> with soft dry tissue.

Never use rough tissue, abrasive cleaning products (powder, cream or steel wool), high-acidity products such as LYSOL, or powerful chemical cleaning products solutions containing chlorine or hydrochloric acid.

Repairs

For more extensive repairs, send a photograph of your WETSTYLE product to our Customer Service Department (service@wetstyle.ca), who will inform you as to the most appropriate methods to use.

WARRANTY

The warranty on WETSTYLE products covers all defects in materials and manufacturing for a period of one year from the date on which the owner originally purchased the product directly from WETSTYLE or from an authorized retailer. This warranty is valid for the original owner only.

This warranty does not apply to cases in which a product was incorrectly installed, or damage due to negligence, misuse, scuffs or scratches, surface corrosion (chemical or natural), cigarette burns, flames, natural catastrophes or other accidents.

WETSTYLE is not responsible for costs and claims that may arise from purchase of a product unsuited to the structure of the existing building. Any transformation or alteration made to a WETSTYLE product automatically voids the warranty. The manufacturer's warranty is limited to repair or replacement (with a product of equal value), provided the claim is made to an authorized retailer or directly to WETSTYLE within the warranty period. Labour costs, and any other expenses entailed by replacement of a WETSTYLE product, are not covered by the warranty.

WETSTYLE products are certified CSA B45.O, CSA B45.4, IAPMO-ANSI Z124.1 and IAPMO- ANSI A124.3.

WETSTYLE 3

